

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B01D 45/16, B04C 3/00, 3/04	A1	(11) International Publication Number: WO 97/49477 (43) International Publication Date: 31 December 1997 (31.12.97)
--	----	---

(21) International Application Number: PCT/NL97/00350

(22) International Filing Date: 24 June 1997 (24.06.97)

(30) Priority Data:
1003408 24 June 1996 (24.06.96) NL

(71)(72) Applicant and Inventor: SWANBORN, Rombout, Adriaan [NL/NL]; Kemperbergerweg 39, NL-6816 RN Arnhem (NL).

(74) Agent: LAND, Addick, Adrianus, Gosling; Arnold & Siedsma, Sweelinckplein 1, NL-2517 GK The Hague (NL).


(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published*With international search report.**In English translation (filed in Dutch).*

(54) Title: METHOD AND DEVICE FOR TREATING OF A GAS/LIQUID ADMIXTURE

(57) Abstract

Method and device for treating a gas/liquid mixture, the device comprising: an inlet (A) for infeed of the mixture; a flow element (4) placed in the line of the inlet and having one or more swirling members (5) to cause turbulence of the mixture; an outlet (8) placed in the line of the flow element for outfeed of the gas flow having liquid at least partially removed; one or more feedback lines (B, D) for discharge of the separated liquid and a part of the gas flow, wherein the feedback lines are connected onto a channel (12) arranged centrally (6) in the flow element; and anti-creep flow means (7) for preventing creep flow along the flow element.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LJ	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

**METHOD AND DEVICE FOR TREATING OF A
GAS/LIQUID ADMIXTURE**

5

Gas/liquid separators generally take a bulky form in order to make certain that the separation efficiency required in determined conditions is ensured. In practice however, problems occur in difficult conditions, such as high operating pressures, high viscosity of the liquid or in conditions where the space is limited, such as occur for instance in offshore oil fields. Poor gas/liquid separators can considerably impair the production yields of oil fields.

10

The present invention provides a device for treating a gas/liquid mixture, comprising:

15

- an inlet for infeed of the mixture;
- a flow element placed in the line of the inlet and having one or more swirling members to cause turbulence of the mixture;

20

- an outlet placed in the line of the flow element for outfeed of the gas flow having liquid at least partially removed;

25

- one or more feedback lines for discharge of the separated liquid and a part of the gas flow, wherein the discharge line is connected onto a channel arranged substantially centrally in the flow element and wherein close to the end of the channel an anti-creep flow element is arranged for preventing creep flow of liquid.

30

In contrast to existing separating devices wherein a mixture flows through a set of parallel plates or through a layer of net-like wires or wherein use is made of a traditional cyclone wherein liquid is introduced therein radially, the present device has extremely compact dimensions, achieves a high separation

efficiency which does not depend (or depends little) on liquid viscosity, has an extremely low pressure drop and/or a wide-ranging option of decreasing the flow rate (turn down ratio).

5 The anti-creep flow means are preferably formed by an anti-creep flow element close to the end of the channel. It is however also conceivable to arrange such anti-creep flow means at another location in the device according to the present invention or to have them formed
10 by a determined dimensioning of the flow element and/or the swirling members and/or by preselected values of the flow speed of the mixture and/or the pressure ratios in the device according to the present invention.

15 The present invention further provides a method for treating a gas/liquid mixture, wherein a device according to any of the foregoing claims is applied.

 The present invention likewise relates to a system for treating a gas/liquid mixture from a bored well in the earth's crust, comprising:

20 - an outer pipeline which is lowered into the bored well;

 - an inner pipeline which is arranged in the outer pipeline while leaving clear a radial space; and

25 - a plurality of parallel placed gas/liquid separating devices which are arranged in the radial space and which each comprise an inlet for infeed of the mixture, a flow element placed in the line of the inlet and having one or more swirling members to cause turbulence of the mixture, the outlet placed in the line
30 of the flow element for outfeed of the gas flow having liquid at least partially removed and one or more feedback lines for discharge of the separated liquid and a part of the gas flow.

35 Partly due to the extremely compact dimensions, devices according to the present invention can herein be disposed in considerable numbers in a circular arc between the casing and the tubing in a borehole, whereby so-called decks are formed, while a plurality of such

decks can likewise be placed in series for separation of for instance 99.5% of the liquid and the gas.

In the sub-claims further steps are designated for an extremely compact embodiment of the device according to the present invention, in addition to the method wherein use is made of one or more such devices.

Further advantages, features and details of the present invention will be elucidated in the light of the following description with reference to the annexed drawing, in which:

fig. 1 shows a partly broken away view in perspective of a first preferred embodiment of a device according to the present invention; and

fig. 2 shows a view in perspective of a modified component for the device of fig. 1.

A device 1 (fig. 1) comprises a substantially cylindrical wall 2 which bounds a flow space 3. Placed in flow space 3 is a flow body 4 which is provided on its outer periphery with curved swirling blades 5 and in the interior of which is arranged a channel 6. A creep interrupter 7 is arranged on the top end of channel 6. Under an outlet opening 8 the device 1 is provided with elongate slots 9.

During operation of the device or cyclone 1 according to the present invention a mist of gas and liquid (droplets) is supplied in the direction of arrow A into the flow space 3, whereafter this liquid flow acquires a cyclone-like flow pattern due to swirling blades 5. Due to the centrifugal force the liquid particles are moved at least to a considerable extent radially out of the gas flow via the longitudinal slots 9 in the direction of arrows B, together with for instance 20% of the quantity of gas, while the remaining gas flow with at least a large part of the liquid removed leaves the device in the direction of arrow C via outlet opening 8. Gas flows B are fed back, as indicated with broken lines D, to a secondary inlet 11 which connects onto a channel 12 to the internal channel 6 in the flow body 4.

This secondary gas flow in the direction of arrows B and E serves to increase the efficiency of discharge of solid particles such as dust particles, and thus also contributes toward cleaning of the gas flow.

5 Owing to the cyclone action of the swirling blades a relatively low pressure is present at the outlet of internal channel 6, whereby the secondary, fed back gas flow is drawn in by the main flow.

10 It has been found in practice that close to the transition of the outlet channel of flow body 4 and space 3 creep flow of liquid can take place along the surface thereof due to the relatively low pressure there, which would mean that this liquid would be carried along by the fed back gas flow and would enter the outfeed flow C. In
15 order to prevent this undesired effect a creep flow interrupter 7 is arranged in the device according to the present invention which deflects the liquid flow outward along the flow element 4 so that the liquid can be carried along by the turbulence current on the outer side of
20 the flow body.

In the shown preferred embodiment of fig. 1 the creep interrupter takes the form of a hollow truncated cone, while in the embodiment of fig. 2 a creep interrupter element 17 takes the form of a substantially flat
25 dish.

The extremely compact device according to the present invention causes only a very small pressure drop in the flow of the mixture of for instance 30 mBar, brings about a high separating efficiency and is not
30 susceptible to great changes in operating conditions. Manufacturing costs for a device according to the present invention can be extremely low.

The present invention is not limited to the above described preferred embodiments thereof; the rights
35 applied for are defined by the following claims.

CLAIMS

1. Device for treating a gas/liquid mixture, comprising:
- an inlet for infeed of the mixture;
 - a flow element placed in the line of the inlet and having one or more swirling members to cause turbulence of the mixture;
 - an outlet placed in the line of the flow element for outfeed of the gas flow having liquid at least partially removed;
 - one or more feedback lines for discharge of the separated liquid and a part of the gas flow, wherein the feedback lines are connected onto a channel arranged centrally in the flow element; and
 - anti-creep flow means for preventing creep flow along the flow element.
2. Device as claimed in claim 1, wherein the anti-creep flow means are formed by an anti-creep flow element close to the end of the channel.
3. Device as claimed in claim 1 or 2, wherein the anti-creep flow element extends radially at least some distance outward relative to the outlet opening of the channel.
4. Device as claimed in claim 2, wherein the anti-creep flow element has a truncated cone shape.
5. Device as claimed in claim 2 or 3, wherein the anti-creep flow element is at least partly disc-shaped.
6. Device as claimed in any of the foregoing claims, wherein the swirling members comprise swirling blades curved in flow direction.
7. Device as claimed in any of the foregoing claims, wherein roughly 2% of the gas flow is fed back.

8. Device as claimed in any of the foregoing claims, wherein the internal diameter of the channel amounts to 2 mm or more.

5 9. Method for treating a gas/liquid mixture, wherein a device as claimed in any of the foregoing claims is applied.


10 10. System for treating a gas/liquid mixture from a bored well in the earth's crust, comprising:

- an outer pipeline which is lowered into the bored well;

- an inner pipeline which is arranged in the outer pipeline while leaving clear a radial space; and

15 - a plurality of parallel placed gas/liquid separating devices which are arranged in the radial space and which each comprise an inlet for infeed of the mixture, a flow element placed in the line of the inlet and having one or more swirling members to cause turbulence of the mixture, the outlet placed in the line of the flow element for outfeed of the gas flow with
20 liquid at least partially removed and one or more feedback lines for discharge of the separated liquid and a part of the gas flow.

25 11. System as claimed in claim 10, wherein a device as claimed in any of the claims 1-8 and/or a method as claimed in claim 9 is applied.



INTERNATIONAL SEARCH REPORT

Inte rnational Application No
PCT/NL 97/00350

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 B01D45/16 B04C3/00 B04C3/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 B01D B04C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 81 01961 A (MARCO GEISSMANN) 23 July 1981 see page 8, line 21 - page 9, line 18; claims; figures 3,4 ---	1-9
Y	EP 0 436 973 A (NEDERLANDSE GASUNIE) 17 July 1991 see column 3, line 15 - column 4, line 47; figure 1 ---	1-9
A	US 4 197 102 A (K.R. DECKER) 8 April 1980 see figure 3 ---	1-11
A	WO 93 05339 A (VATTENFALL UTVECKLING) 18 March 1993 see figure 3 -----	1-11

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "A" document member of the same patent family

Date of the actual completion of the international search

1 October 1997

Date of mailing of the international search report

08.10.97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Bogaerts, M

INTERNATIONAL SEARCH REPORT

information on patent family members

Int. .onal Application No

PCT/NL 97/00350

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 8101961 A	23-07-81	BE 887068 A FR 2473349 A GB 2090163 A,B NL 8120002 A SE 8105377 A	04-05-81 17-07-81 07-07-82 01-12-81 10-09-81
EP 436973 A	17-07-91	NL 8902978 A AT 156724 T CA 2031327 A DE 69031267 D NO 175569 B US 5129931 A	01-07-91 15-08-97 03-06-91 18-09-97 25-07-94 14-07-92
US 4197102 A	08-04-80	NONE	
WO 9305339 A	18-03-93	SE 502765 C AU 2370892 A JP 6509982 T SE 9102519 A US 5466272 A	08-01-96 05-04-93 10-11-94 04-03-93 14-11-95